

iMG1500 Series

FTTH MULTISERVICE GATEWAYS



The AT-iMG1525 and AT-iMG1505 multiservice gateways, new members of the Allied Telesis iMG family, provide enhanced performance for routing and NAT traffic management.

The Allied Telesis iMG1500 Series intelligent Multiservice Gateway is the ideal FTTH customer premise device for the delivery of communications and entertainment services, including carrier-class telephony, high-speed Internet access, IP television, and interactive, two-way video-based services. All of these services are provided over an active optical distribution network via a single optical fiber to the home. The combined delivery of IP Triple Play services — voice, video and data — benefits both service providers and their customers. Service providers can quickly deliver advanced services such as fast Internet, VoIP, IPTV and Video on Demand in a scalable way with complete remote management. End-users benefit by having a single device interconnecting all peripherals, computers, analog and VoIP telephones to a single broadband uplink.

Voice over IP

The iMG1500 Series offers two FXS ports, leveraging Allied Telesis existing SIP and MGCP Voice over IP (VoIP) protocol implementation and established interoperability with major softswitch vendors. The iMG1500 Series supports the connection of modems and faxes to voice interfaces for business applications in SoHo environments. VoIP QoS is assured through Type of Service (ToS) bits and IEEE 802.1p priority tagging. The addition of silence suppression and local generation of comfort noise results in excellent voice quality.

Key Features

- » 1 x 100/1000BX WAN port
- » 5 x 10/100/1000T LAN ports
- » Two FXS ports (AT-iMG1525 model only)
- » USB host and USB slave for console
- » Bi-directional fiber WAN interface
- » Plug-and-play fiber outlet
- » SIP and MGCP VoIP protocol support
- » Major softswitch manufacturer compatibility
- » Class 5 services
- » Support for analog and VoIP phones
- » IP Triple Play ready
- » Stateful Inspection Firewall / NAT
- » DMZ support
- » Access Control List
- » AlliedView NMS support
- » TR-069
- » RoHS compliant

IP Television

The iMG1500 Series is optimized for IP video streaming. The iMG snoops IGMP packets in-transit allowing simultaneous delivery of multiple multicast transmissions such as movie or TV channels. This enables multiple high-quality, high bit-rate video streams without impacting data traffic or IP telephony while delivering the fast channel change that users expect from video services. MPEG video service management and diagnosis is possible through dedicated commands.

Data Delivery and Security

The iMG1500 Series supports industry leading Quality of Service (QoS) through ISO Layer 2 and 3 prioritization techniques including priority tagging with IEEE 802.1p, Type of Service and DSCP fields. Extensive support for per port and per VLAN rate-limiting in the iMG1500 Series enables service providers to deliver tiered data services for the wide spectrum of end customer profiles, providing maximum flexibility in

service differentiation. The hardware is Q-in-Q capable. Security is assured by an integral Stateful Inspection Firewall with NAT to protect end-user networks.

Management and Deployment

The iMG1500 Series is designed to be easy to deploy and manage. With the AlliedView™ NMS software platform, the iMG1500 Series can be remotely provisioned and managed. The iMG1500 Series supports TR-069 and can be managed via an Auto Configuration Server (ACS).

Optical WAN Interfaces

The iMG1500 Series offers single-strand (bi-directional) optical fiber links for FTTH application. The independent passive unit (AT-iMG001), where the optical cable is terminated, allows easy installation, maintenance and replacement thanks to a plug-and-play optical connection. It also provides a locking mechanism to secure the active unit.

Specifications

Hardware

5 x 10/100/1000T (RJ-45)
 2 x VoIP FXS ports (RJ-11)
 1 x 100/1000BX single-strand single-mode
 1 x USB slave for console
 1 x USB host

Optical Interfaces

IEEE 802.3ah 100/1000BX-U single-strand single-mode (SC)
 (20 km): TX 1310 nm; RX 1550 nm
 Max sensitivity -23 dBm
 Max input power -3 dBm
 Max output power -2 dBm

Ethernet

Layer 2 wire-speed packet switching
 Tag-based IEEE 802.1Q VLANs (max 32)
 IEEE 802.1Q tag insertion and stripping
 Port mirroring of ingress/egress traffic
 DHCP client, server and relay
 4K MAC address FDB

WAN Protocols

PPPoE (future)
 Global IP address pool
 DNS proxy
 Static and dynamic IP address assignment

Routing and Multicast

PPP and IP routing
 RIPv1 and v2 (future)
 IGMPv2, v3
 IGMP snooping
 IGMP proxy

Security

NAT
 Stateful Inspection Firewall
 Dynamic port opening
 Access Control List
 IPSec/VPN pass through
 PAP/CHAP authentication (future)

QoS

IEEE 802.1p prioritization
 Programmable ingress/egress rate limiting
 Four QoS queues per port
 DSCP/ToS

VoIP Protocols

SIP 2.0
 MGCP/NCS 1.0

VoIP Features

G.711 a-law and μ -law 64kbps
 G.729 8kbps
 G.726 16/24/32/40kbps
 G.168 ECAN 8-32 msec
 T.38 fax relay
 RTP voice packet encapsulation
 Automatic fax/modem detection
 Voice Activity Detection (VAD)
 Comfort Noise Generation (CNG)
 Packet loss concealment
 Adaptive jitter buffer

5 REN
 Caller ID
 Call transfer
 Call forwarding (unconditional, on busy, on no answer)
 Call waiting
 Call hold
 Message waiting
 3-way call (local RTP MUX future)
 DTMF relay
 RFC 2833

Management

AlliedView NMS
 Telnet
 Remote software upgrade
 Web GUI
 CLI
 SNMP v1, v2
 TR-069

Status LEDs

Power
 WLAN Link/Activity
 Link Link/Activity
 VoIP Use/Activity
 LAN Link/Activity

Power Characteristics

Typical power consumption: 18W
 External power supply
 Input: 100-240V AC, 50-60 Hz
 Output: 12VDC, 1.5A

Environmental Specifications

Operating temperature 0°C to 40°C (32°F to 104°F)
 Max operating humidity 80% relative humidity
 (non-condensing)
 Storage temperature -20°C to 70°C (-4°F to 158°F)
 Max storage humidity 95% relative humidity
 (non-condensing)

Physical Characteristics

Dimensions (W x D x H) 24 cm x 15 cm x 4.5 cm
 (9.5 in x 5.9 in x 1.8 in)
 Weight 400 g / 14 oz

Approvals

CE and UL marking
 Safety IEC/EN60950-1
 UL 60950-1
 EN60825-1
 CAN/CSA-C22.2 No 60950-1-03
 Emission FCC Part 15 Class B
 EMC Directive 2004/108/EC
 EN 55022 Class B
 EN 300 386
 Immunity EN 55024

Ordering Information

AT-iMG1505-xx
 FTTH multiservice gateway

AT-iMG1525-xx
 FTTH multiservice gateway with POTS
 1 x 100/1000BX, 5 x 10/100/1000T, 2 x FXS,
 1 x USB host, 1 x USB slave (includes AT-iMG001
 fiber outlet with locking mechanism)

Related Products

AT-iMG001
 Fiber outlet with locking mechanism (10 pieces)

AT-iMG008-xx
 Battery backup

AT-iMG016
 Battery backup cable

Where xx = 10 for U.S. power supply
 20 for U.K. power supply
 40 for Australian power supply
 50 for European power supply



the solution : the network

Americas Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

EMEA Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

alliedtelesis.com

© 2011 Allied Telesis, Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.
 617-000394 Rev A

Core Telecom Systems partnered with Allied Telesis
 (888) 375-8826 www.coretelecom.net